

Crimping Pump

ELECTRIC HYDRAULIC PE-NUT

30 cu. in./min
Two-Speed

Extremely durable yet lightweight and operate under low-line voltage conditions.

PUMPS

PE-NUT PUMP — 115V

- 5/8 hp universal electric motor (50/60 cycle)
- Two-stage pump for rapid ram advance
- Operational under low-line voltage conditions
- Optional operating pressures available; consult Power Team for details
- Designed for use with spring-returned remote tools
- High-pressure safety relief valve
- Remote hand control with 10-foot cord
- Carrying handle
- Factory filled oil reservoir
- Pressure matched quick-coupler supplied
- Optional carrying case
- Two-stage pumping system
- Unique, intermittent duty pump, piston-type high-pressure pump supercharged by a low-pressure pump.



CAUTION: DESIGNED FOR CRIMPING APPLICATIONS ONLY! This system should not be used for lifting.

Order No.	Oil Delivery per min.	Oil Reservoir qt.	Usable Oil qt.	Overall Width in.	Overall Length in.	Overall Depth in.	Pump Weight w/Oil lbs.
PE-NUT PE-NUTC*	(160 in ³ @ 100 psi 30 in ³ @ 10,000 psi)	1.61	0.75	6.5	14.38	8.25	28

*Includes Case

Electrical Data

Electric Motor

5/8 hp, 10,000 rpm
115V AC, 50/60 Hz
11 amp current draw
(115V @ 10,000 PSI)

Electrical Control

Remote control with 10-foot cord